

Aluminum Electrolytic Capacitor – JMQ

FEATURES


- Warranty of 5000 hours at 105°C



SPECIFICATIONS

Items	Performance Characteristics	
Rated Voltage Range (V)	350V, 400V, 450V	
Operating Temperature Range (°C)	-40°C ~ +105°C	
Capacitance Tolerance (20°C, 120Hz)	±20%	
Dissipation Factor (20°C, 120Hz)	0.15	
Leakage current (µA)	0.01CV or 5mA, whichever is smaller. (at 20°C, after 5 minutes) C: Nominal capacitance (µF) V: Rated voltage(V)	
Load Life (+105°C)	Time	5000 hours
	Leakage Current	Not more than the specified value.
	Capacitance Change	Within ±15% of the initial value
	Dissipation Factor	Not more than 175% of the specified value.
Shelf Life (+85°C)	Time	1000 hours
	Leakage Current	Not more than the specified value.
	Capacitance Change	Within ±15% of the initial value
	Dissipation Factor	Not more than 175% of the specified value.
After Test: U _R to be applied for 30 minutes, 12 to 24 hours before measurement		

DIMENSIONS (mm)



ΦD	51	64	77	90
F	22	28.6	32	32

MULTIPLIER FOR RIPPLE CURRENT

Frequency coefficient

Frequency(Hz)	50,60	120	3 0	1K	≥10K
Factor	0.7	1.0	1.1	1.3	1.4

Temperature coefficient

Temperature(°C)	+40	+60	+70	+85	+1085
Factor	3.8	3.0	2.5	2.0	1.00

Please visit our website to get more update data, those data & specification are subject to change without notice.

Aluminum Electrolytic Capacitor – JMQ

CASE CODE (mm)

L D	53	64	65	75	83	96	100	105	109	115	121	130	131
36	A5	--	A6	--	A8	--	A10	--	--	--	A12	--	--
51	--	C7R	--	C8R	C8	C10R	C10	--	C11	C12R	X12	C13R	--
64	--	--	--	--	--	D10R	D10	D11	--	D12R	D12	D13R	--
77	--	--	--	--	--	E10R	--	--	--	E12R	E12	E13R	--
90	--	--	--	--	--	--	--	--	--	--	--	--	F13R
101	--	--	--	--	--	--	--	--	--	--	--	--	--

L D	144	145	155	157	160	161	171	175	195	196	236	237
36	--	--	--	--	--	--	--	--	--	--	--	--
51	--	--	--	--	--	--	--	--	--	--	--	--
64	D15	--	D16R	--	--	--	--	--	D20R	--	--	--
77	E15	--	E16R	--	E16	--	E17R	--	E20R	--	--	--
90	--	F15	--	F16R	--	F16	F17R	--	--	F20R	F24R	--
101	--	--	--	--	--	--	--	G18R	--	G20R	--	G24R

CASE CODE (mm)

Cap	WV	350		400		450	
	SV (V)	400		450		500	
1000	C8R	3.9	C8R	3.9	C10R	4.2	
1200	C8R	4.2	C10R	4.6	C12R	5.0	
1500	C10R	5.2	C12R	5.6	C13R	5.9	
1800	C10R	5.7	C13R	6.4	D10R	6.3	
2200	C13R	7.1	D10R	6.9	D12R	7.4	
2700	D10R	7.7	D12R	8.2	D13R	8.6	
					E12R	8.7	
3300	D12R	9.1	D13R	9.5	D16R	10.2	
					E13R	10.1	
3900	D13R	10.4	D16R	11.1	D20R	12.3	
							E12R
4700	D16R	12.2	D20R	13.4	E16R	12.9	
							E12R
5600	D20R	14.6	D20R	14.6	E20R	15.4	
							E13R
6800	E16R	15.5	E16R	16.5	F20R	18.0	
8200	F16R	18.1	F16R	18.1	F20R	19.8	
10000	F16R	19.9	F20R	21.7	F24R	23.6	
12000	F20R	23.8	F24R	25.8	--	--	
15000	F24R	28.8	--	--	--	--	

Ripple Current (Arms) 105°C 120Hz

Case code

Please visit our website to get more update data, those data & specification are subject to change without notice.